

U.S. PATENT APPLICATION
FOR
SYSTEM, METHOD AND ARTICLE OF
MANUFACTURE FOR ENHANCING ELECTRONIC
MESSAGES

5
10
15

INVENTORS:

Ian E. Smith

Victoria M. Bellotti

ASSIGNEE: XEROX CORPORATION

HICKMAN STEPHENS COLEMAN & HUGHES, LLP

P.O. Box 52037

Palo Alto, CA 94306

Telephone (650) 470-7430

SYSTEM, METHOD AND ARTICLE OF MANUFACTURE FOR ENHANCING
ELECTRONIC MESSAGES

5

By Inventors:

Ian E. Smith

10

Victoria M. Bellotti

FIELD OF THE INVENTION

15 The present invention relates generally to electronic messaging and, more particularly,
to enhancing electronic messages capable of being transmitted over a network.

BACKGROUND OF THE INVENTION

20 Electronic mail has revolutionized the way that people do business. It has provided
an alternative to many of the traditional communication mechanisms that were
utilized in the past. These include fax, mail and telephone. However, it electronic
mail has traditionally lacked the capability of automated tracking, followup and
other management functions associated with communications that were monitored
25 and traditionally rendered by human intervention. There is a need for a new method
of processing electronic mail which overcomes the aforementioned limitations.

SUMMARY OF THE INVENTION

006138007 071000

A system, method and article of manufacture are provided for managing information
5 transmitted utilizing a network. Initially, a first message is directed to at least one
recipient utilizing a network. Such electronic message includes content. Next, the
first message is stored in a database. Thereafter, the first message is transmitted to
the at least one recipient utilizing the network. In operation, a query is received
from a user utilizing the network. In response thereto, content is retrieved that
10 satisfies the query from the database. The retrieved content is subsequently
transmitted to the user in a second information exchange utilizing the network.

In one embodiment of the present invention, information coupled with the message
is stored in the database. As an option, one or more applications are executed. Such
15 applications can include lead tracking, job requisitioning, event planning, task list
management, project management, and accountability. Further, a reply to the
message can be utilized to advance the processing of a task.

In another embodiment of the present invention, information in the database is
20 utilized to summarize the interaction between one or more participants. Preferably,
a task list is generated to summarize the interaction. Events may also be utilized.
An event can be utilized to organize information from the database. Another event
can be utilized to advance the processing of a task. Further, a reply to the message
can be utilized to generate another message to obtain information for the database.

25 In yet another embodiment of the present invention, the first and second messages
may each comprise an electronic-mail ("e-mail") message. Further, the first
electronic message may include an attachment to the e-mail message. Still yet, the
electronic message may have one or more attributes. An index may also be
30 generated that is based on the one or more attributes of the electronic message after
which the index is stored in the database.

In still yet another embodiment of the present invention, the content may be categorized into a plurality of categories. Further, retrieval of the information from the database may be permitted according to at least one of the categories. As an option, summaries of the information stored in the database may be generated based
5 on the analyzed content. Such summaries may also be stored in the database. At least one of the summaries may also be retrieved from the database utilizing the network.

A platform in accordance with a preferred embodiment provides a base of
10 functionality that application developers can use to add value to email messages. Further, the platform provides a set of reusable, programming abstractions that conceal the details of delivering application functionality in email. This functionality allows application developers to focus on the particular business process they are trying to automate without being concerned about the underlying
15 processing.

The final part of an application in accordance with a preferred embodiment is a set of work objects. Each of these objects is modeled with a java class. A work object describes a unit of work in the system, perhaps analyzing a mail message for some
20 string or sending a message to a project manager. Work objects are created by your application anytime that you desire to perform a complex computation. This structure is a bit more work for the application developer, but allows the platform to use queues internally for scheduling work to be done and insuring that work is completed in a timely fashion. Features including redundancy and load balancing
25 are introduced transparently to the application developer utilizing the work objects.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, aspects and advantages are better understood from the following detailed description of a preferred embodiment of the invention with
5 reference to the drawings, in which:

Figure 1 illustrates a representative hardware environment in accordance with one embodiment of the present invention;

10 Figure 2 is a flowchart of an overall process for fast mapping from a document management system to a relational database in accordance with an embodiment of the present invention;

15 Figure 3 is a flowchart of a process for mapping properties of a document to a relational database in accordance with an embodiment of the present invention;

Figure 4 is an illustration of an exemplary table in accordance with an embodiment of the present invention;

20 Figure 5 is an illustration of an exemplary unstructured table in accordance with an embodiment of the present invention;

Figure 6 is a flowchart of a process for performing property group maintenance in accordance with an embodiment of the present invention;

25 Figure 7 is a flowchart of a process for utilizing partial loading to retrieve properties from the database;

30 Figure 8 illustrates a method for managing information transmitted utilizing a network in accordance with an embodiment;

Figure 9 is a system diagram showing the manner in which an e-mail channel between two recipients is interposed in accordance with a preferred embodiment;

5 Figure 10 is an architecture diagram that shows the orientation of a preferred embodiment with respect to other platform and application layers;

Figure 11 illustrates the manner in which a given application is likely to use the Thinkdoc platform, including the core application and some services, as well as some type of web development platform;

10

Figure 12 is a detailed network architecture that shows the way that a system according to an embodiment of the present invention exists on the public Internet;

15 Figure 13 is a diagram of a message processing system in steady state prior to arrival of a message according to an illustrative embodiment of the present invention;

Figure 14 is a diagram of the message processing system of Figure 13 upon receipt of a message;

20 Figure 15 is a diagram of the message processing system of Figure 14 after receipt of the message;

Figure 16 is a system diagram of message processing continued from Figure 15;

25 Figure 17 is a system diagram illustrating addition of a work object and message factory to the message processing system of Figure 16;

Figure 18 is a system diagram for a message processing system according to an exemplary embodiment of the present invention;

30

Figure 19 depicts a process that occurs sometime before the system of Figure 18 accepts the most recent message; and

Figure 20 is a diagram of the message processing system of Figure 18 after receipt of the message.

5

[illegible]

DETAILED DESCRIPTION OF THE INVENTION

A preferred embodiment provides a base of functionality that application developers can use to add value to email messages. In addition, the system provides a set of
5 reusable, programming abstractions that conceal the details of delivering application functionality in email. This functionality allows application developers to focus on the particular business process they are trying to automate without being concerned about the underlying processing. A set of work objects are each modeled with a java class. Each work object describes a unit of work in the system, perhaps analyzing a
10 mail message for some string or sending a message to a project manager. Work objects are created to perform a set of complex computations. This structure is a bit more work for the application developer, but allows the platform to use queues internally for scheduling work to be done and insuring that work is completed in a timely fashion. Features including redundancy and load balancing are introduced
15 transparently to the application developer utilizing the work objects.

In accordance with a preferred embodiment, a fast implementation of a propertyed document management system to a relational database is utilized to provide data support. One of ordinary skill in the art will readily comprehend that other
20 databases could be interchanged to provide similar capability. In general, this approach groups sets of properties together into relational tables for achieving relational speeds, but allows more dynamic control than traditional Relational Database Management Systems (RDBMS). With this approach, related properties can be associated with a document and then mapped as a group.

25 Techniques for managing large collections of persistent electronic documents are also utilized in an alternative embodiment. Each document has a set of associated named properties that describe the document. One may think of a document's property set as corresponding to the instance variables of an object or the attributes
30 of a database record. One problem that may be found in large-scale document management is the ability to find documents based on queries over their associated

properties. Another problem may be the difficulty in providing end-users the ability to customize the property sets of individual documents or sub-collections of documents. This ability can be very useful if the customization can occur at any time (i.e., after the document has been created and has had an initial set of properties associated therewith). In the past, the implementation of document property sets has either provided good query and update performance with essentially no customization ability, or good customization ability with relatively poor query and update performance. In contrast, embodiments of the present invention provide a process for persistently storing document property sets that provides substantial benefits in flexibility while still providing good performance.

One idea behind the invention is the ability to associate property groups with individual documents. A document may have any number of property groups. Property groups may overlap (i.e., more than one property group may contain the same property) and may be associated with a document at any time. Properties within a group are clustered as much as possible. That is, property groups are stored in the underlying database in such a way that they are physically retrieved and updated together.

This definition of property group may result in several advantages. First, the clustering may help to reduce the overhead of performing retrieval and update operations on properties. Most of the latency of fetching a small amount of data (e.g., a few property values) from the database is due to the round-trip through the network client/server interface. Applications tend to access and/or update more than one property in a group within a short period of time, but tend not to access multiple groups as frequently. Therefore, segmenting a document's properties into related groups tends to reduce the number of network round-trips while reducing the raw amount of data transmitted unnecessarily. As a second advantage, the property group may provide a way in which application programmers can express that a semantic relationship exists between the properties within the group. A document can have zero or more property groups, giving programmers the ability to add

properties in a modular fashion. A third advantage is that property groups may be fully dynamic and can be added or deleted at any time.

sub
A1

5 A preferred embodiment of a system in accordance with the present invention is preferably practiced in the context of a personal computer such as an IBM compatible personal computer, Apple Macintosh computer or UNIX based workstation. A representative hardware environment is depicted in Figure 1, which illustrates a typical hardware configuration of a workstation in accordance with a preferred embodiment having a central processing unit 110, such as a
10 microprocessor, and a number of other units interconnected via a system bus 112.

The workstation shown in Figure 1 includes a Random Access Memory (RAM) 114, Read Only Memory (ROM) 116, an I/O adapter 118 for connecting peripheral devices such as disk storage units 120 to the bus 112, a user interface adapter 122 for
15 connecting a keyboard 124, a mouse 126, a speaker 128, a microphone 132, and/or other user interface devices such as a touch screen (not shown) to the bus 112, communication adapter 134 for connecting the workstation to a communication network 135 (e.g., a data processing network) and a display adapter 136 for connecting the bus 112 to a display device 138.

20

sub
A2

The workstation typically has resident thereon an operating system such as the Microsoft Windows NT or Windows/95 Operating System (OS), the IBM OS/2 operating system, the MAC OS, or UNIX operating system. Those skilled in the art will appreciate that the present invention may also be implemented on platforms and
25 operating systems other than those mentioned. A preferred embodiment is written using JAVA, C, and the C++ language and utilizes object oriented programming methodology. A relational database system is utilized in a preferred embodiment, but one of ordinary skill in the art will readily comprehend that other database systems can be substituted without departing from the claimed invention.

30

Figure 2 is a flowchart of an overall process 200 for fast mapping from a document management system to a relational database. Properties of a document are mapped to a relational database in operation 202. Maintenance of the property groups in the database is performed in operation 204. Partial loading is utilized to retrieve
5 properties of documents stored in the database in operation 206.

In general, applications written against a propertied document-management system may be divided into two broad classes: weak and strong. A weak application may be considered as those applications that utilize the "free flowing" nature of the
10 storage system to read or write properties on documents that are not (or cannot be) anticipated in advance. Such applications exploit the properties of the storage system similar to a dynamically-typed programming language—the ability to decide at run-time the attributes of an object or document. Some examples of this class of application include Dourish's Vista document browser, and Lamping and Salisbury's
15 Packrat browser. In both examples, documents can be organized by the addition of properties of the user's choosing, and thus properties read and written by the application cannot be determined in advance.

A strong application, speaking broadly, is the type of application that uses the
20 property system as a more "structured" store of information. This class of applications is classified as strong because they exploit those properties of the document management system that are most similar to a strongly-typed programming language. Strong applications know what information (stored in properties) they will need and how it has to be structured for their correct operation.
25 Frequently, strong applications are exclusively interested in documents with properties (or, more commonly, collections of properties) that they created or have been explicitly informed about. Examples of strong class could be an email server and reader. The documents of interest are known to be electronic mail (email) messages, and thus specific properties are "expected" for correct functioning, such
30 as "from," "date," and "message-id." Further, these exemplary applications share an

understanding of what an email message was by agreeing to collaborate on the names and value types of the properties involved in email sending and receiving.

- Arising from weak and strong classes are types of hybrid classes. First, there are
- 5 strong applications that become weak once a particular set of data is located. For example, a mail application may allow the user to add arbitrary properties to mail messages. This is the first type of hybrid application - it finds the documents of interest in a strong way, but then allows some types of weak operations on them. The second type of hybrid is a hybrid document. Such a document participates in
- 10 the functioning of at least one strong and one weak application. For example, opening a mail message document in a weak application such as Packrat allows the document to be modified in a weakly-structured way, while the document remains suitable for use with a strong, and ignorant of Packrat, email application.
- 15 Triggering events
- Manual & automatic
 - Synchronous v. asynchronous
- Events
- 20 Property groups or data
- Addition
 - Deletion
 - Modificiation
- 25 Property groups provide the programmer with a means of declaring sets of semantic relationships between properties. A preferred embodiment allows potentially overlapping property groups which are used as hints to the underlying storage system to cluster properties together physically. An embodiment of this clustering takes the form of mapping each property to a distinct column in a table of a
- 30 relational database. Physical clustering facilitates more efficient retrieval and update

of sets of properties when it is known that they will be typically retrieved or updated at the same time.

5 The fact that property groups can overlap means that the mapping from property groups to the underlying storage system must handle this situation. Many of the possible specific mappings from declared groups of attributes to relational tables are part of the prior art in object-relational mapping systems. For example, there are many variations on the basic technique of storing the instances of each class in an object system as a separate table in a relational database. However, since most
10 object systems do not allow classes to share instance variables, there are additional complications that are addressed in accordance with a preferred embodiment that cannot be handled by any prior art techniques.

15 The mapping of property groups into the underlying storage system is a flexible and dynamic approach to physical clustering. The organization of the columns of a table in a relational database system is typically managed by a database administrator that has been granted special privileges. Such management includes the definition and modification of classes in an object-oriented database management system. When the physical organization of a table or class changes, then some explicit step must be
20 executed by the privileged administrator. This is because such structural changes may have negative effects on the performance and/or the correctness of applications which are using the database. In accordance with a preferred embodiment, the programmer only sees documents, properties and property groups. The precise physical mapping of properties into the underlying storage system is hidden from the
25 programmer (although the programmer does know that mapping hints have been provided to the storage system in the form of property group declarations). Therefore, the property-based document management system is free to change the mapping at any time.

30 Since the physical organization of the property groups is hidden from the programmer, multiple mappings can be used to store a given property group. For

- example, if the underlying storage system is in the process of reorganizing a property group from mapping *A* to a new mapping *B*, the document management system can query the data stored using both mappings and combine them to produce the desired answer. This enhances the availability of the overall document
- 5 management system. In prior art systems, physical reorganization of a relational table or object collection implies a privileged data definition command that has a negative impact on concurrent access to the data being reorganized.
- 10 What follows from these classes and hybrids is a set of algorithms to map weak, strong, and hybrid applications on to a relational database while giving excellent performance. In particular, applications which are either strong or a strong-weak hybrid should get performance characteristics that are quite similar to applications written to use a relational model, a very "strong" type of data storage. This
- 15 performance may be achieved without sacrificing the flexibility of the property-storage programming model.

- Property groups are a set of property names and property value types grouped together for a program's use. In one aspect, they may be encoded in a Java class-"in code" - although the idea works with other encodings. For example, a common property group is the set of properties that structure information for browsing. This group might be written something like this:
- 20

- Browser.name: java.lang.String
- 25 • Browser.size: java.lang.Integer
- Browser.creation: java.util.Date

- It should be clear from this property group, called "Browser," that many applications and their associated documents may wish to participate in this structure. Indeed any
- 30 document that is created by an application probably will have this structure applied to it. A document may have any number (including zero) such property groups

applied to it simultaneously and the set of property groups may be changed at any time. If *several* property groups are applied to a document simultaneously, then any property names that they share must have compatible types (Note: this sharing of property names allows a rough form of inheritance in the property space). If
5 incompatible property groups are applied, the first attempt to enforce a property group that is incompatible with existing groups will be rejected.

In applying a property group to a document, the application or programmer applying the group is entering into a contract with the document management system that all
10 of these properties will exist on the document and that the types of the values will be at least (in the object oriented sense of a type relationship) the types mentioned. In the case above, a browsing application and a mail program can coordinate through Browser to display good-looking information to the user, and be sure that the information will be accessible to the other program.

15 In one embodiment of the present invention, applications that use property names that appear in any property group may be required to obey the rules of the property group, even though the application may be unaware of or not using that group. In such an embodiment, the namespace of properties may need to be carefully
20 protected to avoid unexpected failures of applications that "stumble onto" a part of the property namespace that has a property group structure imposed on it. However, this is not the only possible route to take on this issue - it is possible to allow weak applications to use any property names and enforce the property group rules only when the property group is applied. Pragmatically, the latter approach may simply
25 delay the problem of collisions in the property namespace until the property group is applied.

Mapping to a Relational Database

30 Figure 3 is a flowchart of a process for mapping properties of a document to a relational database in operation 202. See Figure 2. With reference to Figure 3, in

operation 302, a database is provided having a plurality of tables relating to a plurality property groups. Each property group in the database has a set of properties associated therewith. In the database, property groups having at least one common property with one another are grouped into a common table while property groups having no common properties are grouped into separate tables in the database. When a document having one or more properties is provided in operation 304, a determination is made as to which of the property groups in the database apply to the document in operation 306. The properties of the document are then mapped in operation 308 to those tables in the database which include a property group that has been determined to apply to the document.

In an aspect of the present invention, each property group may have a set of columns in the table in which the respective property group is grouped. In another aspect of the present invention, the determining which of the property groups apply to the document may be determined by comparing the properties of the document with the set of properties of each property group. In such an aspect, a property group may apply to the document if one of the properties of the document is included in the set of properties of the respective property group.

The following assumes that the reader has a basic understanding of relational database concepts such as tables, rows, and columns. Under a basic approach, each property group is structured as a set of columns in a table, with each document that has the property group applied to it having one row in that table. Property groups that are disjoint in the property namespace are kept in separate tables and property groups that share property names are kept in the same table.

Figure 4 is an illustration of an exemplary table 400 in accordance with an embodiment of the present invention. The table includes a plurality of columns including a Document ID column 402, a Browser.name column 404, a Browser.size column 406, a Browser.creation column 408, and an isBrowser column 410. The isBrowser column 410 in the table 400 is used to distinguish documents that have

had the property group applied to them from those that have not. Since the semantics allow a document to have each of the properties in a weak way in addition to having the property group's strong structure, one may have to do extra bookkeeping to know if this property group is being enforced. The last row 412 of the table 400 shows that an application has placed the property "Browser.size" on document 712 but has not chosen to use the property group "Browser."

Figure 5 is an illustration of an exemplary unstructured table 500 in accordance with an embodiment of the present invention. Because some, perhaps even many, properties will not be participants in any property group, a table may be stored that has these "unstructured" properties. Such a table may be referred to as an unstructured table. In an unstructured table, each row is roughly a property name-value pair. In the exemplary unstructured table 500 illustrated in Figure 5 includes four columns: a Document ID 502 column, a Property Name column 504, a Property Value Column 506, and a Hash column 508. In this table 500, two unstructured properties 510, 512 are on document 209, and one 514 is on document 10472. The values of unstructured properties may be stored as serialized Java objects in SQL Blobs in the column Property Value. The Hash column 508 of this table 500 may be used to make equality queries fast. In one aspect of the present invention, the Hash value may be determined by calling the "hashCode()" method on the java object that is the value of the property. Since the database cannot interpret the serialized object in the value column when evaluating a query, one can use the hash value column (that is understood by the database) to give a conservative estimate of equality. This may require that some false positives be removed after the database does an evaluation involving data in this table.

Property Group Maintenance

Under the present system, the storage management layer may have to do significant processing whenever a previously unknown property group is used. In general, this process can be broken into two primary steps. First, determine if the new property group overlaps-shares properties with-any existing property group. Second, create a

new table for this property group or alter another table if this property group overlaps another.

5 Figure 6 is a flowchart of a process 204 for performing property group maintenance in accordance with an embodiment of the present invention. After the database management system receives an additional property group (having a set of properties associated therewith) to be added to the database in operation 602, a determination may be made in operation 604 as to whether the additional property group has any properties in common with the preexisting property groups of the database. If it is
10 determined that the additional property group has no properties in common with the preexisting property groups of the database, then a new table may be created in the database relating to the additional property group in operation 606. If, on the other hand, it is determined that the additional property group has at least one property in common with at least one of the preexisting property groups of the database, then, in
15 operation 608, one or more of the preexisting tables in the database may be modified to accommodate the additional property group.

In one aspect of the present invention, the modification can involve relating the additional property group to each preexisting table that is related to a preexisting
20 property group in the database having at least one common property with the property group. If the additional property group has been related to more than one table in the database because of sharing common properties with two or more preexisting property groups related to two or more unrelated tables, then all of the modified tables that have been related to the additional property group may then be
25 merged into a single table in the database.

The previous section (Mapping to a Relational Database) describes the simple case of a single property group mapping to a single table. In many situations, several property groups may map to the same relational table. This mapping is desirable
30 because it allows each property (a column in the table) to appear exactly once in all the tables it is involved in. This "each property appears once" strategy minimizes

consistency problems that can occur if each property group had its own copy of a particular property that was intended to be shared.

5 When addressing the issue of determining the overlap between property groups, the storage layer may keep track (in a table in the relational database) of all properties and what property group or groups they appear in. When a new property group is encountered, there are three cases: First, the simplest case of no overlapping properties. In this case, a new table is created for the property group. In a second case, the property group overlaps only one other property group, in which the
10 existing table is modified with columns to accommodate the new property group.

In the third case, the new property group overlaps more than one other property group. In this case, each table representing an existing property group that overlaps the new group is merged with another, until only one table is left. The merged
15 table's columns is the union of all the existing tables that were overlapped, plus the columns that were added to accommodate the new property group. The data in the existing tables is copied over into this new, larger table in such a way that every document occupies exactly one row. This process may end up unioning rows that were previously in disjoint tables. It is important to remember that this new, merged
20 table can represent up to N property groups, but since each represented property group will have a column like "isBrowser" in the example above, it is possible see which of the N property groups a given document is participating in, even though they are contained in one relational table.

25 It should be noted that as an option, this strategy for property group maintenance does not have to "undo" the process above when all documents have been removed from a given property group.

Partial Loading

30 In one embodiment of the present invention, making the performance of applications faster may be accomplished by exploiting the particular features of the relational

model that make database management systems fast. For example, exploiting the fast behavior of an RDBMS to perform reads of all the rows of a given table or selected rows from a given table.

- 5 However, in another embodiment of the present invention, partial loading may be utilized to retrieve properties more quickly. Figure 7 is a flowchart of a process 206 for utilizing partial loading to retrieve properties from the database in accordance with an embodiment of the present invention. Partial loading can be performed upon receiving a query for retrieving a document having one or more particular
- 10 properties associated therewith in operation 702. A determination may then be made as to which of the property groups includes the one or more queried properties in their set of properties in operation 704. In operation 706, all of the properties of the document that are mapped to the property groups determined to include the one or more queried properties in their set of properties may then be retrieved from the
- 15 database. If the one or more properties of the query are determined not to belong to any of the property groups of the database, then all of the properties of the document that are not mapped to any property group of the database may be retrieved from the database in operation 708.
- 20 In general, a standard relational model separates different data sets into tables. Thus, reading a particular table gives no information about other tables. (it is possible to infer information via relational joins.) In contrast, partial loading under the present document management system treats the "atom" of the storage system to be a document, not a row. When a document is "read in" or "found," the assumption
- 25 of the programming model is that all parts of that document are accessible, or known. For example, the programming model allows the programmer to ask, "What are all the properties of this document?" Clearly, if all the information is spread out between different tables as, it may be difficult (and most likely slower) to look at all the tables to find all the properties of a given document.

To alleviate this problem, a lazy strategy for loading is utilized. The Bantam APIs allows one to ask for "all documents that meet this query and have this property group." In this, very common, case, only the part of the relevant documents that can be found in the table that represents the property group is loaded. In the case that
5 other properties are accessed on this document at a later time, extra bookkeeping (in a table in the relational database) may be used to discover all the property groups that the given document participates in. Should the property accessed be part of a property group, that property group's entire set of properties is loaded. This may be done to avoid needless database round-trips and to exploit the locality that is likely
10 to be encouraged by property groups: "if you used property A in property group P, then the chances you'll access property B in property group P is high."

If a property is accessed that is not part of any property group (an "unstructured" or "weak" property) then all the weak properties for this document may be loaded from
15 the database. Since there may be little locality to these accesses, this approach helps to avoiding about one-half the communication costs by loading all the weak properties when any weak property is accessed (e.g., the one-half savings is versus loading the properties individually with a database round-trip for each).

20 OOP is a process of developing computer software using objects, including the steps of analyzing the problem, designing the system, and constructing the program. An object is a software package that contains both data and a collection of related structures and procedures. Since it contains both data and a collection of structures and procedures, it can be visualized as a self-sufficient component that does not
25 require other additional structures, procedures or data to perform its specific task. OOP, therefore, views a computer program as a collection of largely autonomous components, called objects, each of which is responsible for a specific task. This concept of packaging data, structures, and procedures together in one component or module is called encapsulation.

To date, Web development tools have been limited in their ability to create dynamic Web applications which span from client to server and interoperate with existing computing resources. Until recently, HTML has been the dominant technology used in development of Web-based solutions. However, HTML has proven to be

5 inadequate in the following areas:

- Poor performance;
- Restricted user interface capabilities;
- Can only produce static Web pages;
- Lack of interoperability with existing applications and data; and
- 10 • Inability to scale.

Sun Microsystems's Java language solves many of the client-side problems by:

- Improving performance on the client side;
- Enabling the creation of dynamic, real-time Web applications; and
- 15 • Providing the ability to create a wide variety of user interface components.

With Java, developers can create robust User Interface (UI) components. Custom "widgets" (e.g., real-time stock tickers, animated icons, etc.) can be created, and client-side performance is improved. Unlike HTML, Java supports the notion of

20 client-side validation, offloading appropriate processing onto the client for improved performance. Dynamic, real-time Web pages can be created. Using the above-mentioned custom UI components, dynamic Web pages can also be created.

25 ³⁴⁶_{A346} Sun's Java language has emerged as an industry-recognized language for "programming the Internet." Sun defines Java as: "a simple, object-oriented, distributed, interpreted, robust, secure, architecture-neutral, portable, high-performance, multithreaded, dynamic, buzzword-compliant, general-purpose programming language. Java supports programming for the Internet in the form of platform-independent Java applets." Java applets are small, specialized applications

30 that comply with Sun's Java Application Programming Interface (API) allowing developers to add "interactive content" to Web documents (e.g., simple animations,

A3
page adornments, basic games, etc.). Applets execute within a Java-compatible browser (e.g., Netscape Navigator) by copying code from the server to client. From a language standpoint, Java's core feature set is based on C++. Sun's Java literature states that Java is basically, "C++ with extensions from Objective C for more
5 dynamic method resolution."

Sub A4
Figure 8 illustrates a method 800 for managing information transmitted utilizing a network. Initially, in operation 802, a first message is directed to a recipient utilizing a network. Such electronic message includes content. Next, in operation
10 804, the first message is stored in a database. Thereafter, the first message is transmitted to the a recipient utilizing the network. See operation 806. In operation 808, a query is received from a user utilizing the network. In response thereto, content is retrieved that satisfies the query from the database, in accordance with operation 810. The retrieved content is subsequently transmitted to the user in a
15 second message utilizing the network. See operation 812.

In one embodiment of the present invention, information coupled with the message is stored in the database. As an option, one or more applications are executed. Such applications can include lead tracking, job requisitioning, event planning, task list
20 management, project management, and accountability. Further, a reply to the message can be utilized to advance the processing of a task.

In another embodiment of the present invention, information in the database is utilized to summarize the interaction between one or more participants. Preferably,
25 a task list is generated to summarize the interaction. Events may also be utilized. An event can be utilized to organize information from the database. Another event can be utilized to advance the processing of a task. Further, a reply to the message can be utilized to generate another message to obtain information for the database.

30 In an embodiment of the present invention, the first and second messages may each comprise an electronic-mail ("e-mail") message. Further, the first electronic message may include an attachment to the e-mail message. Still yet, the electronic

message may have one or more attributes. An index may also be generated that is based on the one or more attributes of the electronic message after which the index is stored in the database.

- 5 In yet another embodiment of the present invention, the content may be categorized into a plurality of categories. Further, retrieval of the information from the database may be permitted according to at least one of the categories. As an option, summaries of the information stored in the database may be generated based on the analyzed content. Such summaries may also be stored in the database. At least one
10 of the summaries may also be retrieved from the database utilizing the network.

Introduction to the Thinkdoc System

- Thinkdoc, or thinkdoc.com, is a service that adds application value to normal electronic mail messages. The user of thinkdoc applications does not need to install
15 new email or Web browser tools to use the applications. Figure 9 is a system diagram showing the manner in which an e-mail channel between two recipients is interposed in accordance with a preferred embodiment.

- The service works by interposing itself in the email channel between two recipients. In Figure 9, thinkdoc.com 900 is shown to have been interposed between two users,
20 Alice 902 and Bob 904. Although the users may "think" that their mail is traveling from Alice to Bob, it is in fact traveling from Alice 902 to thinkdoc.com 900 and then to Bob 904. This allows ThinkDoc to perform processing on the message as it "passes by" the ThinkDoc server. One or both parties may be aware that ThinkDoc is involved in the transportation of the message, but generally it is of little concern to
25 Alice 902 or Bob 904 as it is "transparent" to them.

The "ThinkDoc system" is really two quite distinct parts. First is the *platform*--the underlying technology--that handles processing messages and other core technical issues. The second part includes a set of *applications* that add value to the customer

and utilize the platform's services. We are going to address this part of the system, applications, first as these are easier to understand.

Applications

- 5 The discussion will begin by explaining a simple example application called "tracker." The tracker application allows a user, here called Alice, to keep track of whether or not her email has been responded to by another user, here called Robert. For this example, it is assumed that Alice has previously "signed up" with ThinkDoc and knows how to use the tracker application.

10

5/26/95

- Alice sends email using her normal email program to Robert. The only difference is that she uses her "nickname" for Robert, "Bob," that she set up with ThinkDoc. By doing this, she invokes the tracker application on the particular message she sends. The email will be transported via ThinkDoc and ThinkDoc will take note of the message. Robert then receives the email as he normally would, with no easily noticeable differences. (If Bob is a sophisticated user and deeply interested, he could discover that Alice is using the ThinkDoc application.)
- 15

- If Robert does not respond within three days, ThinkDoc sends a message back to Alice to inform her that her message was not responded to and that some further action may be necessary. If Robert does respond within the time limit, ThinkDoc takes no action. No matter when Robert replies to Alice's message, the reply reaches Alice exactly as Robert would expect.
- 20

- While tracker is a simple application, the key fundamentals behind ThinkDoc should be made clear. First, neither Alice nor Robert needs to be running special software to use the application. Two, value is being added to the existing email "channel" by
- 25

interposing a service—presumably that Alice pays for—in between receiver and sender.

Applications

5 ThinkDoc includes several applications. . A first application according to one embodiment of the present invention is a simple response tracking application, which is similar to the example given above. Another application provides performance appraisal process automation. This application automates the collection of activities from employees, possible peer reviews of employee's work, and
10 preparation of a final report by a manager.

Yet another application provides employee recruiting automation. This application automates the process of collecting leads, following up with leads to create candidate employees, collecting necessary documents for interview, and finally
15 following up after an interview. The application can also be utilized as a “carrot and stick” that reminds a recruiter to go to a conference and reminding him or her to recruit. Further, this application can be used to audit that a recruiter actually met with and recruited individuals. In addition, templates can be utilized to set up the application based on the requirements of the hirer's particular needs. Accordingly, a
20 particular user defines a particular set of parameters using a template.

A lightweight task and project management application can also be provided. Such an application allows email to be used to organize projects, keep track of tasks (as well as the person accountable for these tasks), and track project status. A sales
25 application can also be provided, such as, for example, lead tracking for Value Added Remarketing by a reseller.

Another application is a travel preparation application. This application can be used for travel authorization. Events can be triggered such that when someone signs up for a travel conference, they will be reminded to document their recruiting activities.

5 *The Core Processor*

There is another part of the system that is not on the list above, the "core" processor. There are some pieces of functionality that are so basic to the functioning of a reasonable system that they must be present. For example, every user of thinkdoc is given a "basic email address" such as joe@thinkdoc.com. One might think that a message to a basic address would be handled by some application, but this "low level" functionality is actually a part of platform in general, the core processor in particular. The core processor can be thought of as part of the platform itself.

The Platform

15 Figure 10 is an architecture diagram that shows the orientation of a preferred embodiment 1000 with respect to other platform and application layers. The ThinkDoc platform 1004 is a technology layer, as shown in Figure 10, that sits above the java platform 1006 and below the ThinkDoc applications 1002. The ThinkDoc platform 1004 provides a base of functionality that application developers
20 can use to add value to email messages. Further, the platform 1004 provides a set of reusable, programming abstractions that conceal the details of delivering application functionality in email. This allows application developers to focus on the particular business process they are trying to automate with being concerned about the underlying processing.

25

The platform is preferably written entirely in Java and thus should be portable to any computing environment that supports the Java 2 standard edition. It has been tested on Windows (98, NT4, and 2000) as well as Solaris 7. Java can be used for all development.

Developers building ThinkDoc applications can use the ThinkDoc toolkit to develop their application. This toolkit is part of the platform and is an object-oriented class library that provides the abstractions mentioned above. It provides support, for example, for describing incoming email messages that an application wants to receive and outgoing messages that the application wishes to send. The (Java) interfaces supported by this toolkit are intimately linked with the platform; for example, the platform's notion of a message template that describes the types of messages that an application might send is described by the interface MsgTemplate.

10 To send a message using the platform, an application writer must use the MsgTemplate interface, although they can specialize this for their purposes.

This toolkit can also be extended to also support the notion of "services" that are based on the platform. Services are abstractions that can be used to develop applications but, unlike the toolkit, they cross application boundaries. For example, a particular user of the ThinkDoc system may use both the lightweight task and project management application and simple response tracking application and would like his or her contact list to be the same for each. A "service" should be used here, since it is likely that the application writers of these two applications did not plan to be utilizing this same information. More importantly, if a new application gets written later that needs a contact list, this "contact service" can facilitate keeping all three applications "synchronized" from the user's point of view. In other words, the platform should support the sharing of some abstractions across applications and this is done with services.

15
20

25

Another such service is a versioning service that allows applications to find versions of documents—generally sent as attachments—that were sent via some other application. To continue the Alice and Robert example discussed above, suppose Alice uses the simple response tracking application as explained above and has

attached the first draft of a proposal in her message to Robert. Robert responds, and attaches a new version of the proposal. They decide together to begin using the task and project management application of ThinkDoc to manage this project. One of them now sends a message about the project with yet a third version of the document and it arrives at the task and project management application. It may be extremely useful for the application author of the task and project management application to be able to ask the ThinkDoc platform, in effect, "Has any version of this document passed through ThinkDoc before?" If the old versions can be found, the task and project management application can provide functionality such as browsing old versions of documents and so forth, even though the task and project management application was not involved in processing the previous versions.

The Web Channel

Thus far, the discussion has centered on email. This focus is because email is central to many business practices today and by adding value to email one gives a substantial benefit to users. However, some tasks are awkward in email, such as getting an overview of a project status. The World Wide Web (WWW) provides another "channel" to deliver the application in. Every application can be thought of as having two channels: one email, one web. Different applications have more or less of one channel or other depending on what user need they fulfill.

Application developers can use standard Web application development tools to develop the web channel. Complicating this, however, is that the web channel and the email channel must be "synchronized" from a user's viewpoint. For example, if the user sends email that passes through the some ThinkDoc application, that user will expect to see that message as part of any status report that he or she receives via the Web from that ThinkDoc application.

A More Detailed Picture

Given the previous discussion of ThinkDoc applications, the core processor, the thinkdoc platform, and the Web channel, a more accurate, logical picture of what the ThinkDoc system looks like is presented hereafter. Figure 11 illustrates the manner
5 in which a given application is likely to use the Thinkdoc platform 1002, including the core application 1100 and some services 1102, as well as some type of web development platform 1104.

Network Architecture

10 Figure 12 is a detailed network architecture 1200 that shows the way that the thinkdoc system 1202 exists on the public Internet 1204. This section explains how email and web traffic reaches a ThinkDoc application. It should be noted that the configuration of machines can change day to day, but the principles are fairly constant.

15

Generally, the "thinkdoc system" lives inside the protected area 1206. In this area 1206, there is access to the necessary database and there may be several copies of the system running. For this example, there are four machines that are running copies of the system, A1...A4 1208, 1210. There is also the database server, M2
20 1212.

The machine M1 1214 is crucial to this scheme. This machine protects the data of the system as well as the application from the public internet. This machine 1214 must be "locked down" to keep interlopers out. This machine 1214 is also acting as a
25 mail gateway to the "interior" of the network. When mail arrives that must be processed by thinkdoc 1202, it is first delivered to M1 1214 and then forwarded by M1 1214 to the thinkdoc mail processing code on one of A1 to A4 1208, 1210. This two-hop scheme allows use of a commercial (off the shelf) mail engine on M1 1214 for doing common sanity checking on the messages. For example, by using spam-

filtering software on M1 1214, there is little worry of a spam attack reaching any of the application machines A1 to A4 1208, 1210. This is a very real concern since a major function of thinkdoc is to process email. It could be highly detrimental if large amounts of email began clogging up the processing of legitimate users.

5

Goals

There are two primary goals for an application architecture according to an embodiment of the present invention:

1. Make applications more segregated from the platform of ThinkDoc.
- 10 2. Make application development more rapid, primarily through reuse of common application code.

There are numerous good reasons for the first goal above, and they are relatively obvious. First, segregation of applications from the platform allows parallel
15 development more easily. Before this change, there was no notion in the code of a "platform" that was separate from applications and so "application" development was intermixed terribly with "platform" development. The second good reason for segregation is that it allows one to make the platform scale up to "internet size" and these efforts must be isolated from application development, although they need
20 applications to test with.

With respect to the second goal, the reasons here are fairly clear as well. Prior to utilizing reuse, writing new application code is quite formulaic. Code re-use facilitates the development of new applications, primarily in terms of development
25 speed. An additional benefit of this reuse is that there are fewer points of change for application developers in case the platform developers change the underlying infrastructure.

A ThinkDoc Application

There are four basic parts to a ThinkDoc application, the application object itself, a set of message descriptors, a set of message templates, and a set of work objects.

- 5 The first of these is simply a placeholder for general application information--such as its name. The message descriptors describe classes of incoming messages that need to be handled by this application. It is important to realize that a descriptor describes a class of messages, not a particular message since many users will be sending messages to the system. For example, the class of messages is described by
- 10 a pattern on the "to" line of the email message, i.e. "project-manager-XXXX@projects.thinkdoc.com". The XXXX is the part of the address that changes based on which user is participating in the application. The descriptor describes all the messages of this form.

- 15 The third part of an application is a collection of message templates. These describe outgoing messages that this application sends. Again, a single template models a class of a message, since the particular details of the message are filled in at run-time. In fact, these templates are quite a bit like programs--they have conditionals, loops, etc. to allow the developer to express fairly complex things in the outgoing
- 20 messages. Preferably, there is infrastructure in the system that can take a target email address, a template, and a set of bindings for the variables in the template and transmit a message.

- The final part of an application is a set of work objects. Each of these objects is
- 25 modeled with a java class. A work object describes a unit of work in the system, perhaps analyzing a mail message for some string or sending a message to a project manager. Work objects are created by an application anytime that it is desired to perform a complex computation. This structure is a bit more work for the application

developer, but allows the platform to use queues internally for scheduling work to be done and insuring that work is completed in a timely fashion. Preferably, the platform can introduce redundancy and load balancing transparently to the application developer because of these Work objects.

5

Message Descriptors

The message descriptor class is `com.thinkdoc.app.MsgDescriptor`. This interface sets out the basics of a descriptor. In principle, it has two basic parts. `stemAddress()` which is responsible for deciding if a given address is "covered" by this descriptor and `markUp` which is what to do with messages that are found to be covered by this descriptor.

Since most of the time `stemAddress` and `markUp` want to conspire, there is a user data object that is opaque to the ThinkDoc platform that can be exchanged between them. If the `stemAddress` method returns an object, it is assumed that this is an address that is covered by this descriptor. The returned object will be passed back (later on) in the call to `markUp`. This object is ignored by the platform, so it can be of any type that is useful to the descriptor writer. Using this technique, it should never be necessary to "stem" an email address more than once because the result of the call to `stemAddress` is cached in the returned object.

25 There is a simple implementation of the `MsgDescriptor` interface in the class `com.thinkdoc.app.DescriptorBase`. This class understands that frequently messages have a particular form: `prefix-data@host.ourdomain` where `prefix`, `host`, and `ourdomain` are fixed for the life of the application. An example used in accordance with the performance appraisal process automation application (described above) might be `activity-request-6fzly2@pa.thinkdoc.com` where the prefix is "activity-request," the host is "pa," and the domain is "thinkdoc.com."

Given a prefix and a set of host names (the domain is fixed in this example as "thinkdoc.com"), DescriptorBase is capable of deciding if most messages do **not** meet the requirements of this descriptor. A set of hostnames are allowed because
5 frequently one wants to allow several that are semantically the same such as, "task", "tasks", and "mytasks". When the prefix, one of the hosts, and the domain match, DescriptorBase will call the method getSemanticsForStem which must be implemented by any subclass. To this method is passed the data portion of the to line, with everything else removed, and the subclass can then decide if this "to" line
10 is a "match" based on the semantics it chooses. Whatever is returned from getSemanticsForStem is returned through the stemAddress call as explained above.

It should be noted that other implementations of MsgDescriptor are both possible and useful. These are primarily descriptions in which the format of the to lines is not
15 so regular as those described by DescriptorBase. For example to allow the case of addresses like 7days@thinkdoc.com where any number may be used, a different implementation of MsgDescriptor would be needed.

A further refinement--subclass--of DescriptorBase is the class
20 com.thinkdoc.app.SingletonDescriptor. This class is useful when the incoming mail message uniquely refers to a document in the storage system. This class converts calls on getSemanticsForStem into calls on the method findDocument that must be implemented by the subclass writer. The subclass author should implement this to do a query, find the target document (or not) and return that document as the result.
25 After doing this, the subclass author will receive calls on a different version of the markUp call explored above. This new version hands back the "found document" found in the query that was run in findDocument.

A final node on the inheritance tree that is rooted at DescriptorBase is the class `com.thinkdoc.app.TokenDocDescriptor`. This class is a specialization of `SingletonDescriptor` that can answer whether or not a given to line is covered by the descriptor completely on its own.

5

This class hinges strongly on the class `com.thinkdoc.util.TokenSchema` that allows the creation of documents (see `getUniqueDoc` in this class) that are known to have a property with a unique value. The property is described by the `TokenSchema` class and is the field `token`. Because of this uniqueness property, this descriptor class can
10 check to see if a document with the data portion of a given to line has the same "magic" value as some document currently in the storage layer. In the example above, `activity-request-6fzly2@pa.thinkdoc.com` is such an address. If some document exists with a "token" that is `6fzly2` this descriptor will assert that in fact this to line is covered.

15

Message Templates

A message template is a description of a class of messages that are sent by your application. Most application writers will want to use the base class `com.thinkdoc.app.BasicApp` for their application class as `BasicApp` has some easy to
20 use support for binding a set of message templates to your application.

Since message templates are initially encoded as text files, application writers must keep the text form of their message templates--usually referred to as just "templates" in the `thinkdoc`--in the filesystem. The convention is to keep these files in the
25 content directory and to give them filenames which are the same as their template names (written in the content at the beginning of the file).

The process of converting a text file in the filesystem, a template, into a message template object useable by the ThinkDoc platform is accomplished with the class `com.thinkdoc.msg.TemplateCompiler`. Normally, application writers don't need to worry about this class as the interaction with it is controlled by their superclass,

5 `BasicApp`. In summary, `TemplateCompiler` takes the text representation of a template and compiles it into a "program" that can be run by the infrastructure to emit messages. This "program" is represented by the interface `com.thinkdoc.msg.MsgTemplate`. The `MsgTemplate` class is the one that application writers can use to request the system to send a message.

10

Application writers must be aware that this compilation of the text file template to the "real" `MsgTemplate` object is done only once, at the time the system is bootstrapped. Thus, to change the templates that an application is using requires re-bootstrapping.

15

Returning to the discussion of `Basic`, this base class requires that its subclasses--`ThinkDoc` applications--implement the method `getMessageTemplateName`. This should return an array of strings that are the set of templates this application wishes to use. These names are assumed to correspond to the filenames of these templates

20 in the content directory. If you implement this method, `BasicApp` will take care of compiling templates when the application is bootstrapped and stopping the bootstrap if one of the templates is not correct.

If a message is to be sent from an application, one can request a `MsgTemplate` by

25 name from `BasicApp`. Access to the template is provided with the method `getTemplateByName`. One must follow the convention that a template's filename and its "template name" in its body are the same for this to work properly. This method is searching for a *message descriptor* and the names of message descriptors are computed from the name "inside" the template's content. If a handle to the

application subclass is not readily available, the AppRegistry and the method
getTemplate can be used. This allows one to request a template from any
application; this is quite common (and encouraged) in work objects (see below)
because they usually don't have a pointer to the application object they work on
5 behalf of.

Assuming that a MsgTemplate is obtained from the getTemplateByName call one
can then use the message factory in com.thinkdoc.msg.MessageFactory to send a
message. This, of course, requires a few extra parameters in addition to the
10 MsgTemplate such as who the message is being sent to, what is to appear in the
from line, etc.

Work Objects

Probably the most difficult part of developing applications with the ThinkDoc
15 platform is the use of work objects. Work objects are derived from
com.thinkdoc.app.Work. This class defines the basic interface to a closure, a block
of code and the variables it needs to do its work. Objects derived from Work
perform most of the actions in any ThinkDoc application.

20 Work objects are stored up in the infrastructure on queues. Each queue maintains its
work objects in time order. The time that a given piece of work should be executed
is passed to the Work subclass at the time it is created. By creating work objects that
will execute substantially in the future, it is easy to schedule "reminders" and other
events that are triggered later. The constant, Work.ASAP, indicates that you would
25 like a work object executed at the next available moment.

When a work object is "executed" or "run" the infrastructure will call the method `doWork` on the subclass. This method cannot return any value nor may it throw any exceptions. These restrictions are in place because it is not clear what code will be "running" the work object; there may be no one to return a value or throw an exception to. This method is passed an instance of `com.thinkdoc.smtp.FIFO` which is a simple FIFO into which more work objects may be placed (see `put`). This can be useful if one work object generates more work objects. The user should note however, that FIFOs are not ordered by time (thus the "FIFO" designation) as the `WorkQueue` class is.

10

Since these queues and their contents--the work objects--are long-lived it is necessary for each `Work` subclass to be able to "save itself" onto a document. When the system needs to "store" a queue, perhaps because the system needs to shutdown, it creates a document for each `Work` object. It then asks the `Work` object to write all the necessary information about itself on that document; this is done via the `store` method. When a queue is recovered from storage, the reverse happens. The infrastructure takes a document and calls the static method `load` with the document and expects it to be able to return an instance of the proper subclass of `Work`.

15

At the moment, it may not be known what subtype of `Work` a given document is bound to, this is encoded on a property of the document. This is accomplished by using a magic property, `WORKQUEUE_TYPE_PROPERTY` and giving it a value that is unique to the particular subtype. The subtype is found by modifying `com.thinkdoc.smtp.WorkQueue` in the `load` to invoke the right piece of code.

20

25

In general, work done by work objects will be bound fairly strongly to "events" in an application such as receiving a particular type of message or enough time elapsing to merit sending a reminder to a particular user. This is the reason that the `markUp` described above in the section on message descriptors returns a work object.

Normally, markUp will put some properties on one or more documents ("mark up") and then return a subclass of Work that will do the expensive computation that finishes the job.

5 Examples

In accordance with the foregoing discussion, several examples are set forth below. These examples provide overviews of the ThinkDoc system in operation, in accordance with preferred embodiments of the present invention.

10 *Example 1*

Figure 13 shows the ThinkDoc system 1300 in its "steady state," before a mail message has arrived. For this part of the explanation, assume that the application currently in use is the only one in the system.

Figure 13 shows the application (TA) 1302 linked into the application registry (AR) 15 1304 (com.thinkdoc.app.AppRegistry). This is accomplished via the methods debug() and production() on the registry. The application developer must edit these methods to "let the registry know" about the application. This can also be done with a configuration file. The application 1302 is a subclass of com.thinkdoc.app.AppBase that an application developer has written. AppBase is 20 an implementation of the interface com.thinkdoc.app.MsgApp.

Throughout the Examples section, objects drawn in dashed lines are classes that can be written by application developers. Solid boxes are instances of classes, or subclasses, that are part of ThinkDoc system according to a preferred embodiment of the present invention.

25 Referring to Figure 14, a message 1402 arrives on the SMTP port. It is picked up by ThinkDoc's infrastructure; no application involvement is necessary.

The "To line" on the message **1402** is examined to see if any application is "interested in it." If so, that application will take responsibility for processing that message **1402**. (The process of determining interested applications is covered next.)

Note that this message's to line is checked when the message **1402** arrives at the
5 ThinkDoc server. If no application is interested in the message **1402**, it will be refused entrance to the system ("not accepted" in SMTP parlance) and the mail daemons involved in its delivery will send it back to its origin with an error message. Partly, the checking to find interested applications is done "early" in an effort to defeat spam.

10 An implication of this policy is that the to line must encode enough information for applications to make the "accept or reject" choice. Since the body of the message **1402** has not yet been received, the message's content is not yet available.

In the constructor of the application object, TA, one will have wanted to "connect" the application **1302** with it's descriptors, MD1 **1404** and MD2 **1406**. MD1 **1404** is
15 MessageDescriptor1, a class that has been written and a subclass of com.thinkdoc.app.SingletonDescriptor. MD2 **1406** is MessageDescriptor2, a class that has been written and a subclass of com.thinkdoc.app.TokenDocDescriptor. These describe the "class" of messages that the application finds interesting. A typical constructor might look like this:

20

```
public YAO {  
  
    // this list should never change after  
  
    //we build the app object  
  
    descList.add(new MessageDescriptor1(this));  
  
25 }
```


The application object TA has in its base class the necessary machinery to export the list, descList above, to the registry when needed.

The two bits of text **1408**, **1410** under the message descriptors MD1 **1404** and MD2 **1406** reflect what “type” of messages they can understand. The ? in each is a “don’t
5 care” for matching against the incoming message. The suffix for the hosts is understood to be whatever domain the program is running in--and this need not be thinkdoc.com in some debugging cases.

The application registry, AR, will cycle through all the descriptors of all the applications trying to match the message’s to line against some descriptor. In this
10 case, MD1 **1404** is the match for this incoming message.

Referring to Figure 15, when MD1 **1404** is asked if it matches the presented to line, someone-57@somehost.thinkdoc.com, it will be asked to return an object. This object is represented as a “Blob Of Data” BOD or “any old object” **1502**. This can be any java Object. This object is not interpreted by the ThinkDoc infrastructure
15 itself, it is simply held by the infrastructure to be returned to MD1 **1404** later.

The reason that this is necessary is a subtle implication of a fact that was explained before. Since the message **1402** has not yet been accepted at the time MD1 **1404** “accepts” it, the message **1402** cannot be processed at that time. Later, after the message **1402** has been accepted and some basic processing done on it—such as
20 decoding MIME attachments—the accepted message is presented back to MD1 **1404** for processing.

Since MD1 **1404** may have done significant computation to decide to accept or reject the message **1402** earlier, the result of that computation can be encoded in the BOD **1502** and reused later, avoiding duplicate work. The BOD **1502**, unchanged,
25 will be presented with the message **1402** when MD1 **1404** is given a chance to process the message **1402**.

The two methods 1504 shown in Figure 15 below the bit of text 1408 are methods on the descriptor MD1 1404.

- All Message Descriptors are implementations of the interface `com.thinkdoc.app.MsgDescriptor`. Frequently, as is the case indirectly here with MD1 1404 and MD2 1406, application developers subclass `com.thinkdoc.msg.MsgDescriptorBase` to get a “standard” implementation. This is not required and some application developers may need to implement `MsgDescriptor` directly.
- 10 `stemAddress()` is the method of `MsgDescriptor` that is called to compare an address to see if it matches a descriptor, as discussed above. If that method returns null there is no match, otherwise the returned value becomes the BOD 1502, and the descriptor is understood to match the given email address.
- 15 Because MD1 1404 extends `SingletonDescriptor`, there is an implementation of `stemAddress()` supplied already by the superclass. This matches part of the address—all except the question mark discussed above—and then calls `findDocument()` with possible matching part of the address, in this case “57”.
- 20 `findDocument()` can be implemented by MD1 1404. MD1 1404 should perform an operation on the Bantam to determine a document that is semantically meaningful to MD1 1404 that is uniquely identified by 57. If so, MD1 1404 returns that Document and that Document becomes the BOD 1502. If not, MD1 1404 returns null and the registry will proceed to look for other descriptors that want this message 1402.
- 25 After the message 1402 has been accepted and “decoded” by the ThinkDoc infrastructure, control will return to MD1 1404. In the decoding process a proper Document has been created to hold the message 1402. This Document has many

useful properties on it such as the subject line of the message 1402 and who it is from.

Referring to Figure 16, when control returns to MD1 1404, it may begin doing its particular processing on the message 1402. Because MD1 1404's superclass

- 5 SingletonDescriptor is abstract, MD1 1404 must implement the method markUp() 1602. This method is handed two Documents, one containing the message 1402 in the top left and the other being the BOD 1502, which is known to be a Document in this case.

- 10 The process of working with message 1402 can and sometimes is completed in the markUp method. This is discouraged in a production system, but for development it can be useful for testing understanding. Because you have access to a document of "state," the BOD 1502, and the message that will alter that state you can perform your computations at this point.

15

For performance reasons, one might not want to do large computations in the markUp() method 1602 as this can tie up the SMTP server. A properly written markUp() should return a Work object to allow processing of email to continue, while delaying the processing of this message 1402 until a later, and likely more
20 convenient, time.

- As shown in Figure 17, a Work object (W) 1702 is returned by markUp() 1602, if one is necessary. W 1702 is a Work object, a subclass of `com.thinkdoc.app.Work`. This object is a closure—a collection of code and data necessary to do some computation—that can be held in a queue until the ThinkDoc infrastructure can
25 execute the work. It should be assumed that W 1702 will be executed in very different context from the call on markUp() 1602, such as on another thread, in another address space, or possibly on another machine.

Work objects have a preferred time that they wish to execute. ThinkDoc attempts to honor this time on a best-effort basis. This time can be very short or it can be two weeks in the future—and that is useful for setting a reminder.

- 5 When a Work object **1702** is actually “run” the method `doWork()` is called on that object. In this method, long-running computations can (and should) be performed.

For this example, we’ll assume that the work **W 1702** wishes to send an email message. This is likely some type of “response” to receiving the message **1402**.

- 10 Message templates (MT) **1704** are the way that ThinkDoc applications can send mail, and may be written by a user. Message descriptors are about receiving mail. A message template **1704** is the text of a message to send out, including spots for “variables” that can be supplied at run time.

- 15 Message templates **1704**, or just templates, are stored outside the running system in a textual form. Applications usually keep their templates in a textual form in their development filesystem. At the time a ThinkDoc system is initialized, “bootstrapped,” these templates are compiled into the system in a faster form and cached. Thus to change a template, reinitialization of the system may be necessary.

- 20 A Work object like **W 1702** or a descriptor like **MD1 1404** may ask their application for a `MsgTemplate` instance for a given textual name. `MsgTemplate` objects are instances of `com.thinkdoc.msg.MsgTemplate`, the compiled form of the text specified by the user.

- 25 In the example above, the Work object **W 1702** would ask it’s application object for a `MsgTemplate` of some name, fill in the variables that are needed to “run” the template, and then proceed to send the message.

The MessageFactory MF 1706 is part of the ThinkDoc infrastructure (com.thinkdoc.msg.MessageFactory). When an application wishes to send a message, a message template and a few other parameters are supplied to the MessageFactory 1706 to the actual send procedure. Preferably, applications never
5 send messages any other way.

The template that the Work object 1702 found via the application object is passed as a parameter to the factory 1706. The factory 1706 will need important message fields such as the from line, the subject line, and so forth to do the transmission.

- 10 It is worth understanding that there are several actual implementations of the message transmission hidden by the factory 1706. One is the obvious SMTP implementation, one is a debugging implementation that logs all messages to a file and doesn't actually send them over SMTP, and one is a testing implementation for connection of the messages back to a testing harness.
- 15 No matter which implementation is in use, the W object is unaware of this choice. A key thing that may be supplied with the template to the factory is a set of variable bindings. These are passed as instances of java.util.Map to give values to variables found in the templates.

Example 2

- 20 Figure 18 depicts another illustrative process 1800 for processing a message. In Figure 18, a new message 1802 has arrived with the address: anyone-aoeu1htns2@otherhost.thinkdoc.com. As in example 1, Thinkdoc's infrastructure picks up the message 1702. The application registry AR 1304 walks through all known applications and attempts to find a descriptor owned by an application that
25 "matches" the message's to line.

The focus here is on MD2 1406, a subclass of com.thinkdoc.app.TokenDocDescriptor. Tokens are preferably a commonly used

object in the ThinkDoc system. Basically, a token is a marker that is put on a Document that is guaranteed to be unique throughout the system. This token is a string of letters and numbers, preferably in lower case, that is safe for use in an email address.

5

Commonly, an email address "is related to" a unique document that stored to keep state about the application. The TokenDocDescriptor base class codifies this common use by assuming that the email address section with the ? in the address of interest, anyone-?@otherhost, must match the token on exactly one document. If so, the TokenDocDescriptor implementation will return that document as the value of stemAddress() discussed before. The marked document will become the "blob of data" 1502 and no programmer intervention is required.

Figure 19 depicts a process 1900 that occurs sometime before the system accepts the most recent message. SomeObj 1902 is some application object in the program. TokenSchema 1904 is the class com.thinkdoc.util.TokenSchema, part of the ThinkDoc infrastructure. Storage 1906 is an instance of com.xerox.bantam.Storage, part of the Bantam document management system. The document 1908 labeled aoe1snth2 is a document that is being managed by the Storage object; it has the token on it aoe1snth2.

20

At some point in the past, SomeObj created the document 1908 shown in Figure 19 by calling the method TokenSchema.createUniqueDoc(). This call creates the document 1908 and returns it to the caller. SomeObj 1902 would obviously need to add more properties to that document 1908 to have it hold the state that is necessary for correct functioning later.

25

Referring to Figure 20, it is seen that MD2 1406 has "automatically" found the document that holds the state. This document is the "BOD" 1502 for this message 1802.

This document, along with the mail message 1802, will be passed to the markUp() method 2002 of MD2 1406. The markUp() method 2002 is an abstract method of TokenDocDescriptor, MD2's superclass.

As before, markUp() 2002 should do no long running computations. If such
5 computations are needed, a Work object should be returned to be executed later.

While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of a preferred embodiment should not be limited by any of the above described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

[illegible]